VIRAJ VSPL GROUP

SECURE FIRST™

An ISO 9001 : 2015 Certified Company

TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

## Load Arrester

### Ref: SF-LA-300-10, SF-LA-300-15

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Karabiner (SF-1102) at the Load Arrester end.

**DESIGN**

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Karabiner (SF-1102) at Load Arrester end.
- Galvanized steel wire rope ( option of having S.S. wire rope available)

**LENGTH**

- 10 mtr, 15 mtr.

**CABLE**

- Material: Galvanized steel wire dia 4.8 mm.
- Minimum Breaking Strength: 15 KN

**WEIGHT**

- SF-LA-300-10 :-5.900 kg ± 0.100 kg
- SF-LA-300-15 :- 6.350 kg ± 0.100 kg

**USER CAPACITY**

- User Capacity: 300 kg

**RELEVANT STANDARD**

- As per Machine Directive 2006/42/CE

PRODUCTS LIABILITY INSURANCE 2 Million VIRAJ GROUP

CELEBRATING 1994 29 2023 YEARS
QUALITY I SERVICE I PROFESSIONALISM

A Government Recognized Star Export House

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA

info@virajsyntex.com

www.virajsyntex.com