VIRAJ VSPL GROUP

SECURE FIRST™

An ISO 9001 : 2015 Certified Company

TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

Load Arrester

Ref: SF-LA-400-15, SF-LA-500-15

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Karabiner (SF-1102) at the Load Arrester end.

DESIGN

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Karabiner (SF-1102) at Load Arrester end.
- Galvanized steel wire rope (option of having S.S. wire rope available)

LENGTH

- 10 mtr. to 15 mtr.

CABLE

- Material: Galvanized steel wire dia 6 mm.
- Minimum Breaking Strength: 15 KN

WEIGHT

- SF-LA-400-10 :- 11.420 kg ± 0.100 kg
- SF-LA-400-15 :- 11.900 kg ± 0.100 kg
- SF-LA-500-10 :- 11.420 kg ± 0.100 kg
- SF-LA-500-15 :- 11.900 kg ± 0.100 kg

USER CAPACITY

- User Capacity: 400 kg and 500 kg.

RELEVANT STANDARD

- As per Machine Directive 2006/42/CE

PRODUCTS LIABILITY INSURANCE 2 Million VIRAJ GROUP

CELEBRATING 1994 29 2023 YEARS
QUALITY I SERVICE I PROFESSIONALISM

A Government Recognized Star Export House

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA

info@virajsyntex.com

www.virajsyntex.com