

An ISO 9001 : 2015 Certified Company

Retractable Block Polymer Casing with Webbing & EA

Ref: SF-RFAE-10W, SF-RFAE-12W

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Swivel Steel Snap Hook SF-1404 with energy absorber (EA-4400) at the retractable end.

DESIGN

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 & EN 362:2002 gate strength 3600 lbs.
- 24 mm UHMWPE webbing

LENGTH

- 10 mtr, 12 mtr.

WEBBING

- Material: UHMWPE Webbing.
- Minimum Breaking Strength: 15 KN

WEIGHT

- SF-RFAE-10W :- 5.950 kg ± 0.100 kg
- SF-RFAE-12W :- 6.130 kg ± 0.100 kg

USER CAPACITY

- User Capacity: 100 kg Max.

RELEVANT STANDARD

- Meets or Exceeds EN 360 : 2023



TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS



C-36 UPSIDC Industrial Area, Rooma,
Kanpur- 209402 (UP) INDIA



info@virajsyntax.com



www.virajsyntax.com