VIRAJ VSPL GROUP

SECURE FIRST™

An ISO 9001 : 2015 Certified Company

TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

Retractable Block Polymer Casing with G.I. wire Rope & EA

Ref: SF-RFAE-3.5

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Swivel Steel Snap Hook SF-1404 with Energy absorber (EA 4400) at the retractable end.

DESIGN

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 & EN 362:2002 gate strength 3600 lbs.
- Galvanized steel wire rope.

LENGTH

- 3.5 mtr.

CABLE

- Material: Galvanized steel wire rope 4.8 mm.
- Minimum Breaking Strength: 12 KN

WEIGHT

- SF-RFAE-3.5 :- 2.580 kg ± 0.100 kg

USER CAPACITY

- User Capacity: 100 kg Max.

RELEVANT STANDARD

- Meets or Exceeds EN 360 : 2023

PRODUCTS LIABILITY INSURANCE
2 Million
VIRAJ GROUP

A Government Recognized Star Export House

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA

info@virajsyntex.com

www.virajsyntex.com