VIRAJ VSPL GROUP

SECURE FIRST™

An ISO 9001 : 2015 Certified Company

TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

Retractable Block Polymer Casing with Webbing & EA

Ref: SF-RFAE-5W, SF-RFAE-6W & SF-RFAE-7.5W

Robust, light weight and Durable Polymer, casing made from high impact strength nylon. Has a Swivel Anchorage eye at one end: and a Swivel Steel Snap Hook SF-1404 with energy absorber (EA-4400) at the retractable end.

DESIGN

- Quick activating breaking mechanism component
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 & EN 362:2002 gate strength 3600 lbs.
- 24 mm UHMWPE webbing

LENGTH

- 5 mtr, 6 mtr & 7.5 mtr.

WEBBING

- Material: UHMWPE Webbing.
- Minimum Breaking Strength: 15 KN

WEIGHT

- SF-RFAE-5W :- 3.480 kg ± 0.100 kg
- SF-RFAE-6W :- 6.560 kg ± 0.100 kg
- SF-RFAE-7.5W :- 6.3680 kg ± 0.100 kg

USER CAPACITY

- User Capacity: 100 kg Max.

RELEVANT STANDARD

- Meets or Exceeds EN 360 : 2023

PRODUCTS LIABILITY INSURANCE
2 Million
VIRAJ GROUP

A Government Recognized Star Export House

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA

info@virajsyntex.com

www.virajsyntex.com