VIRAJ
VSPL GROUP

An ISO 9001 : 2015 Certified Company

TALON-LE (SRL) Polymer Casing with GI wire/cable & Energy Absorber

TALON-LE Galvanized Wire Cable SRL-LE (ANSI Leading Edge Rated) with High Impact Strength Polymer Housing with Built-in Handle, swivel eye at anchorage end, other end with load indicator swivel snap hook. Includes one (1) installation Karabiner and one (1) tagline.

Ref: SF-RFA-LE-30FT TO 50FT

DESIGN

- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 gate strength 3600 lbs.
- Galvanized steel wire rope

LENGTH

- 30 ft to 50 ft.

CABLE

- Material: Galvanized steel wire rope Ø7/32 Inches
- Minimum Breaking strength: 3600 lbs.

WEIGHT

- SF-RFA-LE-30 FT :- 15.514 ± 0.22 lbs
- SF-RFA-LE-40 FT :- 15.914 ± 0.22 lbs
- SF-RFA-LE-50 FT :- 16.314 ± 0.22 lbs

USER CAPACITY

- ANSI User Capacity: 310 lbs. Max.

RELEVANT STANDARDS

- Meets or Exceeds ANSI Z359.14-2021 CLASS 2.

PRODUCTS LIABILITY INSURANCE
2 Million
VIRAJ GROUP

A Government Recognized Star Export House

TECHNICAL DATA SHEET
FALL PROTECTION EQUIPMENTS

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA
info@virajsyntex.com
www.virajsyntex.com