

## An ISO 9001 : 2015 Certified Company

### TALON-X (SRL) Polymer Casing with GI wire/cable & additional Handle

Ref: SF-RFA-15FT (N) to SF-RFA-20FT (N)

TALON-X 15 to 20 FT' Galvanized Cable SRL with High Impact Strength Polymer Housing swivel eye at anchorage end, other end with load indicator swivel snap hook. Includes one (1) quarter turn locking Karabiner SF-1101 A(C).

#### DESIGN

- Quick activating breaking mechanism components.
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 gate strength 3600 lbs.
- Galvanized steel wire rope

#### LENGTH

- 15 ft to 20 ft.

#### CABLE

- Material: Galvanized steel wire rope Ø3/16 Inches
- Minimum Breaking strength: 3600 lbs.

#### WEIGHT

- SF-RFA-15FT (N) :- 6.724 lbs ± 0.22 lbs.
- SF-RFA-20FT (N) :- 6.900 lbs ± 0.22 lbs.

#### USER CAPACITY

- ANSI User Capacity: 310 lbs. Max.

#### RELEVANT STANDARDS

- Meets or Exceeds ANSI Z359.14-2021 CLASS 1.

