



An ISO 9001 : 2015 Certified Company

TALON-X (SRL) Polymer Casing with Webbing & Additional Handle

Ref: SF-RFA-15W FT (N) to SF-RFA-20W FT (N)

15 ft to 20 ft Talon-X Lightweight SRL with one (1) Swivel snap hook at anchor end (ANSI). Includes one (1) quarter turn locking Karabiner SF-1101 A (C).

PHYSICAL PARAMETERS

- Quick activating breaking mechanism components.
- Robust & durable plastic casing
- UHMWPE Webbing.
- Lightly visible load indicator at the Swivel snap hook
- Good quality corrosion resistance components.

LENGTH

- 15 ft to 20 ft.

WEBBING

- Material: UHMWPE webbing 0.78 Inches
- Minimum Breaking strength: 5000 lbs.

WEIGHT

- SF-RFA-15W FT (N) :- 5.092 lbs \pm 0.22 lbs.
- SF-RFA-20W FT (N) :- 5.434 lbs \pm 0.22 lbs.

USER CAPACITY

- ANSI User Capacity: 310 lbs. Max.

RELEVANT STANDARDS

- Meets or Exceeds ANSI Z359.14-2021 CLASS 1.



TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS



A Government Recognized
Star Export House



C-36 UPSIDC Industrial Area, Rooma,
Kanpur- 209402 (UP) INDIA



info@virajsyntax.com



www.virajsyntax.com