TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

An ISO 9001 : 2015 Certified Company

DOUBLE PULLEY TRIPOD

Ref: SF-TP-800 (DP)

VIRAJ Tripod has been designed for confined space entry / retrieval applications. Its simplistic design allows the easy set up providing the user a means of controlled ascent and descent in minimal time

FEATURES

- Double integral head mounted pulleys which is permanently incorporated in the cast aluminum head of the Tripod and provides independent passing over of cable from a Winch and a Retrieval Block.
- One auxiliary 5000 lbs eye bolts as atachment points.
- Every Tripod is provided with installed mounting bracket.
- Adjustable height from 45.2” to 84.85”

HOW TO USE

- Refer User Instruction

LOAD CAPACITY

Maximum Load Capacity

- Personal 310 lbs.

MATERIAL

Tripod Legs : Material Alluminium Allow Finish Anodized

Cast Head : Material Alluminium Allow Finish Powder Coated

Eye Bolt & Locking Pins : Material Stainless Steel Finish Polished

WEIGHT

- 28.000 lbs ± 0.2 lbs.

RELEVANT STANDARDS

- 5000 lbs

RELEVANT STANDARDS

- Meets or Exceeds ANSI Z359.18-2017.

LENGTH	SPECIFICATION	COMPLIANCE
7 ft.	▪ Fully adjustable telescopic legs, adjustable height from 45.27" to 84.65". ▪ Wheelbase (Footprint) : 59" Diameter. ▪ Weight : 28 lbs appx. ▪ Maximum load capacity : 500 kgf.	ANSI Z359.18-2017
10 ft.	▪ Fully adjustable telescopic legs, adjustable height from 78.80" to 114.17". ▪ Wheelbase (Footprint) : 71" Diameter. ▪ Weight : 33 lbs appx. ▪ Maximum load capacity : 500 kgf.	

PRODUCTS LIABILITY INSURANCE 2 Million VIRAJ GROUP

A Government Recognized Star Export House

C-36 UPSIDC Industrial Area, Rooma, Kanpur- 209402 (UP) INDIA

info@virajsyntex.com

www.virajsyntex.com