



An ISO 9001 : 2015 Certified Company

TALON-LE DUAL (SRL-P) Polymer Casing
with GI wire/cable & Energy Absorber

TALON-LE Galvanized Wire Cable SRL-LE (ANSI Leading Edge Rated) with High Impact Strength Polymer Housing, swivel eye at anchorage end, other end with load indicator swivel snap hook. Includes one (1). Twin SRL connector (SF-1700)

Ref: SF-RFA-LE-2X8 FT to 8.5 FT

PHYSICAL PARAMETERS >>

- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Swivel Snap Hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 gate strength 3600 lbs.
- Galvanized steel wire rope

LENGTH >>

- 8.0 ft & 8.5 ft.

CABLE >>

- Material: Galvanized steel wire rope Ø 3/16 Inches
- Minimum Breaking strength: 3600 lbs.

WEIGHT >>

- 11.243 lbs. ± 0.22 lbs.

USER CAPACITY >>

- ANSI User Capacity: 310 lbs. Max.

RELEVANT STANDARDS >>

- Meets or Exceeds ANSI Z359.14-2021, CLASS 2.



TECHNICAL DATA SHEET
FALL PROTECTION EQUIPMENTS

